

# **Be unique**Stylish and flawless POS printers



#### Chic

The CT-S251 is perfect for high class restaurants and boutiques where the environment requires a top class POS printer with eye-catching design. Choose between the white or black versions.

#### **Fast**

With its unique and stylish design, the two-inch CT-S251 POS printer is perfect for receipt or queue management systems. With a class-leading 300 mm/s print speed, front exit and compact size, the CT-S251 blends performance and poise.

## CITIZEN CT-S251

**POS** 

#### **Applications**

- Receipts
- Queue management
- Weigh scales
- Coupons
- Daily reports
- Hospitality



#### **Well connected**

Connectivity is key with the possibility for USB, Serial, MFi Bluetooth®, Ethernet and WiFi interfaces and toolkit support for iOS™, Android™ and Windows® operating systems.That creates ideal conditions for easy integration.





### **Easy to use**

Thanks to the robust yet user friendly design, the CT-S251 has quick and efficient paper loading, preventing paper jams.



#### **Specifications**

Model		CT-S251
Printing method		Line Thermal Dot Printing
Printing width		54mm/432 dots
Dot pitch		8 x 8 dots/mm (203 dpi x 203 dpi)
Number of columns		Up to 36 digits (12 $\times$ 24: font A), Up to 48 digits (9 $\times$ 24: font B), Up to 54 digits (8 $\times$ 16: font C)
Printing speed		Max. 300mm/sec., When greyscale printing: 130mm/sec
Line spacing		4.23mm (1/6 inch); adjustable by user comand
Barcode type		UPC-A, UPC-E, JAN / EAN-8, JAN / EAN-13, ITF, CODE39, CODE93, CODE128, CODABAR (NW-7), PDF417, QR Code, GS1 Databar.
Emulation		ESC/POS™®
Paper	Width	57.5 ± 0.5 mm
	Diameter	83mm or less
	Thickness	53µm to 85µm
	Recommended Paper	Mitsubishi Paper Mills P220AG normal type 65, HP220AB-1 highly conserved type 75, F230AA normal type 65, P220AB normal type 85, Oji Paper PD150R normal type 75, PD160R high storage type 65/75, Nippon Paper TF50KR-2Y high storage type 62, TR50KJ-R high-save type 63
Power adapter		37AD2 (AC Adapter)
AC input voltage		AC 100 to 240V, 50/60 Hz, 150 VA
DC operating voltage		24V DC ±7%, supplied by AC adapter
Weight		1.20 Kg
Dimension (W x D x H)		108 x 165 x 108 mm footprint. +5mm front lip
Operating environment		+5 to +45°C, 10% - 90% RH, non condensing
Storage environment		-20 to +60°C, 10% - 90% RH, non condensing

All product names are trademarks of the respective manufacturers.  $ESC/POS^{m}$  are trademarks or registered trademarks of Seiko Epson Corporation. Bluetooth  $^{\mathbb{R}}$  is a registered trademark of the Bluetooth SIG and WiFi is the registered trademark of the Wi-Fi Alliance. Android is a trademark of Google Inc.,  $IOS^{m}$  is a trademark of Cisco Systems. Windows is either a registered trademark of Microsoft Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded.

## CITIZEN CT-S251

**POS** 

#### **Features & Benefits**

- Front Exit
- Fast 300 mm/sec
- 2-inch media:  $57.5 \pm 0.5 \text{ mm}$
- MFi / iOS™ Bluetooth® version
- WiFi and Ethernet versions
- ENERGY STAR® power supply
- Stylish black or white case
- Same height as cash drawers
- Cash drawer connection
- ESC/POS $^{\text{TM}}$ ® compatibility
- SDKs for iOS<sup>™</sup>, Android<sup>™</sup>, Windows<sup>®</sup>

